

## 125 Thermocouple Calibrator

### Features :

- Simple key operation.
- Dual Display LCD.
- Display °C & °F
- Accepts 11 Different Thermocouple types
- Auto Ramp Function
- Universal Mini Plug to accept many standard Thermocouple designs



Input Type	°C	Accuracy With Internal CJC	Accuracy With External CJC
K	-200~-100	+/- 0.5°C	+/- 0.3°C
	-100~1000	+/- 0.4°C	+/- 0.2°C
	1000~1370	+/- 0.5°C	+/- 0.3°C
J	-210~1130	+/- 0.4°C	+/- 0.2°C
T	-250~-150	+/- 0.7°C	+/- 0.2°C
	-150~400	+/- 0.4°C	+/- 0.2°C
E	-250~-100	+/- 0.6°C	+/- 0.4°C
	-100~850	+/- 0.4°C	+/- 0.2°C
R	0~250	+/- 0.7°C	+/- 0.5°C
	250~1760	+/- 0.5°C	+/- 0.5°C
S	0~250	+/- 0.7°C	+/- 0.5°C
	250~1400	+/- 0.5°C	+/- 0.3°C
	1400~1760	+/- 0.6°C	+/- 0.4°C
N	-200~-100	+/- 0.5°C	+/- 0.3°C
	-100~410	+/- 0.4°C	+/- 0.2°C
	410~1300	+/- 0.5°C	+/- 0.3°C
L	-200~-100	+/- 0.5°C	+/- 0.3°C
	-100~900	+/- 0.4°C	+/- 0.2°C
U	-200~600	+/- 0.2°C	+/- 0.2°C
B	600~800	+/- 0.7°C	+/- 0.5°C
	800~1000	+/- 0.6°C	+/- 0.4°C
	1000~1820	+/- 0.5°C	+/- 0.3°C
C	0~150	+/- 0.5°C	+/- 0.3°C
	150~650	+/- 0.4°C	+/- 0.2°C
	650~1000	+/- 0.5°C	+/- 0.3°C
	1000~1800	+/- 0.6°C	+/- 0.4°C
	1800~2310	+/- 0.9°C	+/- 0.7°C

Battery Type	9V Alkaline Battery
Display	4+5 Digit LCD
Operating Conditions	0~50°C Less Than 85% rH
Dimensions	88x165x26mm
Weight	330g
Accessories	Carry Case, Users Manual, Battery, Connector Cable